



Natural Wax & Polish

SPECIFICATION & PROCEDURAL DATA SHEET



DESCRIPTION:

A refined Beeswax & Citrus Oil polish, with pleasant aromatics and emulsified into a ready-to-use paste.

USES:

Polishing internal furniture and joinery that has been previously oiled or waxed. Ideal for cleaning/rejuvenating same and for the upkeep of French-polished/lacquered items. Has excellent woodworking attributes and would seal/polish slate, terracotta, stucco etc.

SPECIAL NOTES:

- a) This product is **NOT** advisable for horizontal woodwork in wet areas such as Kitchens, Bathrooms, Laundries etc. Refer to ORGANOIL **HARD BURNISHING OIL** listed under our **Classic Woodcraft Finishes**.
- b) Should you be considering using this wax over previously stained wood: It would definitely **NOT BE RECOMMENDED** if said stain was surface-residing using pigments/colourants. Should stain used be of the penetrative wood dye process, then given the min. 14 days curing/drying requirement, this wax should be fine for polishing over. Do a trial (in an obscure location) to appraise any degree of colourant disturbance.
- c) For the palest, least-darkening cabinetry finish possible, a double (2) wax application and polish to raw woodwork, (fine-sanded to min. 600-1200 grit - the finer the better), is recommended. Permit a minimum 24 hours between wax applications.

APPEARANCE:

Pale, SATIN sheen with minimal deepening of existing colour/s.

STAINING:

As this product is an emulsified paste it cannot have colourants added to it. Any colour imparting (whether a 'wet look' from a clear oil, or stain effect of wood dye) must be conducted to the raw wood first, though refer **Special Note b)** above.

SIZES AVAILABLE:

250ml, 500ml & 2 litre tubs. For availability visit website home page.

COVERAGE:

Approx. **10** square metres per **250ml** / **20** square metres per **500ml**

PREPARATION:

- 1. a.** If conducting a pale, double-wax finish to raw wood, fine sand surfaces through to min. **600-1200** grit paper (**the finer the better**).
- 1. b.** Where wax-finishing over recent coat of **Olde Style DANISH OIL** (and having permitted min. **14** days curing/drying time to elapse) you should inspect surfaces for raised grain/fibres (very likely on plywoods). Before waxing, remove any evidence of such by sanding through to **600 – 1200** grit paper.
- 2.** Ensure surfaces are clear of sawdust etc. clean and dry.

APPLICATION:

1. Ensure you have understood aforementioned **usage, notes** and **preparation** advice.
2. Apply wax sparingly and evenly to surfaces with clean lint-free cloth (eg. Cotton, linen).
3. Leave under ventilation to go tacky (approx. **5** minutes in WINTER / **15** minutes in SUMMER) then firmly buff/rub over areas with fresh, lint-free cloth. **Note: If your cloth is overly grabbing, you may be approaching the buff/rub too early (wait a few more minutes), OR you may have over-applied wax to areas (rub excess off with white, synthetic scourer/s then buff off).**
4. Where conducting double-wax finish, leave project for min. **24** hours then repeat Application steps **2)** and **3)** as stated.
5. Should you then power buff with lambswool (a further, min. **24-48** hours later) patina improves.
6. Now leave finished project to fully cure/air-dry for **5-7 day** (avoiding spills or objects placed on).

MAINTENANCE:

In the short term, shine can be sustained by simply buffing over with clean, dry cloth. To remove grime from grab/finger marking etc. wipe over surfaces with solution of warm water and methylated spirits (for heavy, built-up grime utilise with synthetic scourers). Once dry, revisit **Application sets 2) and 3)**, though be VERY sparing with wax. **Wax finishes by their nature are prone to water/heat marking, so be selective where you utilise, and be very considerate of their treatment (use coasters, doilies etc.) Sometimes such marking may dissipate over the ensuing days, if not, you may be able to remove by using this wax as a “cutting-agent” in unison with synthetic scourer, then cloth buff over.**

BOTTOM LINE:

A very classy finish, though choose its location use thoughtfully as it requires respectful treatment. ALWAYS use wax sparingly, and finally, you are not excused from referring to can's instruction label for other storage, disposal, health and safety considerations.

CONDITIONS:

OUR INFORMATION IS GIVEN IN GOOD FAITH AND IS BASED ON RESULTS OBTAINED FROM EXPERIENCE AND TESTS. HOWEVER, AS THE ACTUAL END USE OF THESE PRODUCTS IS BEYOND OUR CONTROL, ALL RECOMMENDATIONS ARE MADE WITHOUT GUARANTEE. NO REPRESENTATIVE OR AGENT OF OURS HAS THE AUTHORITY TO WAIVE OR ALTER THESE CONDITIONS.

ORGANOIL PTY LTD ABN 62 052 501 792, PO BOX 377, BYRON BAY AUSTRALIA 2481
PH: (+612) 6685 8896 FAX: (+612) 6685 6747 - WEB SITE: www.organoil.com.au

